




### FR Multipair Unscreened Cables-FR Belden Equivalent 8471

#### » Application

These fire resistant cables are used as high-conductivity copper speaker cables.

#### » Construction

- » Conductor: Tinned copper wire.
- » Insulation: Mica tape+LSZH.
- » Sheath: LSZH.
- » Insulation Colour: Black, White.



#### » Fire Performance

<b>Circuit Integrity</b>	IEC 60331-21; BS 6387 CWZ; DIN VDE 0472-814(FE180); CEI 20-36/2-1; SS229-1; NBN C 30-004 (cat. F3); NF C32-070-2.3(CR1)
<b>System circuit integrity</b>	DIN 4102-12, E30 depending on lay system
<b>Flame Retardance (Single Vertical Wire Test)</b>	EN 60332-1-2; IEC 60332-1-2; BS EN 60332-1-2; VDE 0482-332-1 ; NBN C 30-004 (cat. F1); NF C32-070-2.1(C2); CEI 20-35/1-2; EN 50265-2-1*; DIN VDE 0482-265-2-1*
<b>Reduced Fire Propagation (Vertically-mounted bundled wires &amp; cable test)</b>	EN 60332-3-24 (cat. C); IEC 60332-3-24; BS EN 60332-3-24; VDE 0482-332-3; NBN C 30-004 (cat. F2); NF C32-070-2.2(C1); CEI 20-22/3-4; EN 50266-2-4*; DIN VDE 0482-266-2-4
<b>Halogen Free</b>	IEC 60754-1; EN 50267-2-1; DIN VDE 0482-267-2-1; CEI 20-37/2-1 ; BS 6425-1*
<b>No Corrosive Gas Emission</b>	IEC 60754-2; EN 50267-2-2; DIN VDE 0482-267-2-2; CEI 20-37/2-2 ; BS 6425-2*
<b>Minimum Smoke Emission</b>	IEC 61034-1&2; EN 61034 -1&2; DIN VDE 0482-1034-1&2; CEI 20-37/3-1&2; EN 50268-1&2*; BS 7622-1&2*
<b>No Toxic gases</b>	NES 02-713; NF C 20-454

Note: Asterisk \* denotes superseded standard.



## Special Belden Equivalent Cables

### » Electrical & Mechanical Characteristics

AWG		16
Conductor Construction		19x0.287
UL Style		2598
Maximum Conductor Resistance	Ω/km	15.8
Voltage Rating	V	300
Nominal Capacitance Conductor to Conductor	pF/m	108.3
Bending Radius		19xOverall Diameter
Operating Temperature	°C	-20~80

### » Dimensions

Ordering Code	No. of Pairs	Insulation Thickness	Sheath Thickness	Overall Diameter
		mm	mm	mm
BE118471FR	1	0.584	0.81	7.46