




Multipair Overall Screened Cables-Belden Equivalent 9504

» Application

These multipair overall screened cables have pairs laid up in an aluminum/polyester tape with a tinned copper drain wire. These cables are suitable for RS232 applications, used as audio, control and instrumentation cables.

» Construction

- » Conductor: Tinned copper wire.
- » Insulation: Semi-Rigid PVC.
- » Overall Screen: Aluminium/Polyester tape.



- » Drain Wire: Tinned copper wire.
- » Sheath: PVC (V type)/LSZH (H type).
- » Insulation Colour: Black/Red, Black/White, Black/Green, Black/Blue.

» Electrical & Mechanical Characteristics

AWG		24
Conductor Construction		7x0.2
UL Style		2464
Maximum Conductor Resistance	Ω/km	85
Voltage Rating	V	300
Nominal Capacitance Conductor to Conductor	pF/m	98
Nominal Capacitance Conductor to Screen	pF/m	164
Bending Radius		10xOverall Diameter
Operating Temperature	$^{\circ}\text{C}$	-30~80

» Dimensions

Ordering Code	No. of Pairs	Insulation Thickness	Sheath Thickness	Overall Diameter
		mm	mm	mm
BE119504V	4	0.25	0.81	6.7
BE119504H	4	0.25	0.81	6.7